

EN 353-1



The AC 360 vertical fall protection system is a guided type fall arrester on a rigid vertical line, conform to EN353-1:2014 standard. The system meets the requirements of European Parliament Regulation 2016/425.

The AC360 system consists of a

vertical rope guide made of 8 mm diameter stainless steel rope (ref. AC 850)

The upper end of the rope guide is fitted with a shock absorber (ref. AC 362).

The lower end of the rope guide is fitted with a spring tensioner (ref. AC 910) spring tensioners with rope tension indicator (ref. AC 401 or AC 402).

The upper and lower (with tensioner AC 910) end of the rope guide is fastened to the fixed structure using an AZ 090 screw coupling

every installed guide is equipped with an information plaque (ref. AC 803 / AC 804).

the vertical rope guide with a length over 10 m features a line guide (ref. AC 922) which protects the rope guide against vibrations caused, e.g. by wind.

the slider (ref. AC 363) constitutes a user's individual protection equipment. It is installed on a guide in case of the need to use the safety system. The slider moves along the line up and down during normal user movement, and in case of a fall, locks on the line, halting the fall.

- The system's guide may be tilted forward and to the sides by an angle of no more than 15° in relation to the vertical.

The system is intended for a maximum of 2 simultaneous users with a weight of no more than 140 kg each.

### SPECIAL FEATURES



Protection for maximum user's weight of 140 kg



Protection for 2 users

### PARAMETERS

Max. user weight 140 kg

#### ROPE

Diameter Ø 8 mm

Material stainless steel

#### MECHANISM

Material stainless steel

#### CARABINERS

Carabiner model AZ 030

# AC 360

Vertical fall arrest system

**IMPROVED**

**PROTEKT**<sup>®</sup>

**PROTEKT Grzegorz Laszkiewicz Spolka z o.o.** Starorudzka 9, 93-403 Lodz, POLAND  
KRS: 0001009727 | REGON: 524047958 | NIP: 7292747932

[WWW.PROTEKT.PL](http://WWW.PROTEKT.PL)

**EXPORT SALES DEPARTMENT** Skromna 6, 93-405 Lodz, POLAND  
Phone: +48 42 29 29 500, [export@protekt.com.pl](mailto:export@protekt.com.pl), Fax +48 42 680-20-93